





# Bar Carrier

Permavent



## Physical specification

All measurements in millimetres unless otherwise indicated



Bar Carrier

## Features and benefits

- White PVC glazed-in option
- Provides various levels of equivalent area, based on Slotvent option
- Range of glazing options, suitable for single and double glazed units
- Slimline design requires only minimal glass reduction of 55mm

## Example order:

**BC4HD** + required glazing thickness, e.g. **20mm** + carrier length, e.g. **750mm**

## Models, control options and key data

Product Code	Slotvent	Equivalent area (mm <sup>2</sup> )	Min (mm)	Max (mm)	Glazing width (mm)	Carrier length (mm)	Control	Dn,e,w (dB)
BC4HD	4000HD & 4000HEG	3200	316	1500	4-6, 20, 24, 28	450, 600, 750, 900, 1200, 1500	F	33
BC8HD	8000HD & 8000HEG	6400	588	1500	4-6, 20, 24, 28	600, 750, 900, 1200, 1500	F	31
BCS	4000SB	2700	450	1500	4-6, 20, 24, 28	450, 600, 750, 900, 1200, 1500	B, F, PC	33
BCGB	5000GB	5000 Free Area	430	1500	4-6, 20, 24, 28	450, 600, 750, 900, 1200, 1500	Permanent	n/a

Scottish Building Regulations: Free Area performance (see page 14 for full details)  
 4000HD = 4000mm<sup>2</sup>, 8000HD = 8000mm<sup>2</sup>, 4000S = 4000mm<sup>2</sup>, 5000GB = 5000mm<sup>2</sup>