

Zehnder ComfoTube

Semi-rigid ducting system



Features and benefits

- > Crush resistant
- > Flexible up to 90°
- > No sealants required
- > Easy to clean
- > Easy to cut

Model options

Zehnder ComfoTube:
Ø 75mm
Available in 3 lengths
(2m, 20m & 50m rolls)

Zehnder ComfoTube:
Ø 90mm
Available in 2 lengths
(20m & 50m rolls)

Installation

- 1 Cut the pipe to the required length
- 2 Place the O-ring in the second groove in from the end
- 3 Apply lubrication to the O-ring
- 4 Slide and fix the pipe onto the connecting piece
- 5 Push the fixing slide in to the end

| Zehnder ComfoTube 75mm | Zehnder ComfoTube 90mm | Zehnder ComfoTube connector |
|---------------------------------|---|--|
| 2m roll 20m roll 50m roll | 990 328 081 990 328 001 990 328 007 | 20m roll 50m roll |
| | | 990 328 010 990 328 009 |
| | | Click sleeve 75mm Click sleeve 90mm |
| | | 990 328 107 990 328 109 |



End caps - 10 pieces

| | |
|--------|-------------|
| Ø 75mm | 990 328 262 |
| Ø 90mm | 990 328 263 |



| Plastic manifold | Plastic manifold | Plastic manifold |
|--|------------------|---|
| Ø 125mm connection, 5-port x Ø 75mm | TPDB1255 | Ø 160mm connection, 10-port x Ø 75mm |
| | | TPDB16010 |
| | | Ø 180mm connection, 15-port x Ø 75mm |
| | | TPDB18015 |



| | | |
|---|---|---|
| <p>Housing TVA-P 75</p> <p>Ø 125mm valve to 2 x Ø 75mm tube</p> <p>990 326 121</p>  | <p>Housing TVA-P 75</p> <p>Ø 125mm valve to 2 x Ø 75mm tube</p> <p>990 326 125</p>  | <p>Housing TVA-P75</p> <p>Ø 125mm valve to 1 x Ø 75mm tube</p> <p>990 326 001</p>  |
| <p>Housing TVA-P 90</p> <p>Ø 125mm valve to 1 x Ø 90mm tube</p> <p>990 326 122</p>  | <p>Housing TVA-P 90</p> <p>Ø 125mm valve to 1 x Ø 90mm tube</p> <p>990 326 126</p>  | <p>Housing CLD P 75 - frontal sleeve</p> <p>Height = 85mm Height = 115mm Height = 140mm</p> <p>990 320 810 990 320 812 990 320 849</p>  |
| <p>Housing CLD-P-75 - lateral sleeve</p> <p>Height = 85mm Height = 115mm Height = 140mm</p> <p>990 320 811 990 320 813 990 320 850</p>  | <p>Housing CLD P 90 Frontal sleeve</p> <p>Height = 115mm Height = 140mm</p> <p>990 320 845 990 320 851</p>  | <p>Housing CLD P 90 - Lateral sleeve</p> <p>Height = 115mm Height = 140mm</p> <p>990 320 846 990 320 852</p>  |
| <p>Connecting junction</p> <p>Connects Flat 51 to ComfoTube 90/75mm</p> <p>990 322 013</p> <p><i>Includes 2 x O-rings and locking slides</i></p>  | <p>90° connecting junction</p> <p>Vertical 90° bend for connecting Flat 51 to ComfoTube 90mm</p> <p>990 322 046</p> <p><i>Includes 2 x O-rings and locking slides</i></p>  | <p>Renoventil housing</p> <p>Length 400mm centric, connects to ComfoTube 90mm</p> <p>990 320 062</p>  |
| <p>Rectangular housing</p> <p>1 x Ø 75mm to Lamina or Bilamina 400</p> <p>990 321 641</p> <p>1 x Ø 75mm to Lamina or Bilamina 600</p> <p>990 321 663</p>  | <p>Rectangular housing</p> <p>1 x Ø 90mm to Lamina or Bilamina 400</p> <p>990 321 643</p> <p>1 x Ø 90mm to Lamina or Bilamina 600</p> <p>990 321 661</p>  | <p>Adjustable airflow regulator</p> <p>For Ø 75mm For Ø 90mm</p> <p>990 320 026 990 320 027</p>  |
| <p>O-ring seal - 10 pieces</p> <p>For Ø 75mm For Ø 90mm</p> <p>990 328 362 990 328 363</p>  | <p>Locking slide – 10 pieces</p> <p>For Ø 75mm For Ø 90mm</p> <p>990 326 024 990 326 025</p>  | <p>Rectangular housing</p> <p>2 x Ø 75mm to Lamina or Bilamina 400</p> <p>990 321 642</p> <p>2 x Ø 75mm to Lamina or Bilamina 600</p> <p>990 321 664</p>  |

| Rectangular housing | Lamina grille | Bilamina grille |
|---|------------------------------|------------------------------|
| 2 x Ø 90mm to Lamina or Bilamina 600 | Length 400mm Length 600mm | Length 400mm Length 600mm |
| 990 321 662 | 990 321 740 990 321 760 | 990 321 640 990 321 660 |



| Steel extract valve | Steel supply valve | Plastic extract valve |
|---|----------------------------------|---------------------------|
| Ø 100mm STB-1-100 Ø 125mm STB-1-125 Ø 125mm STB-2-125 | Ø 100mm KE 100 Ø 125mm KE 125 | Ø 100/125mm STC100/125 |
| 705 510 021 705 512 521 705 522 521 | 990 326 251 990 326 252 | 705 051 021 |



| Coanda effect supply valve | High induction supply valve | High induction supply valve |
|----------------------------|---|---|
| Ø 90mm, plastic | Ø 125mm, for CLFR/ TVA, plastic STH-1-125 | Ø 125mm, for CLFR/TVA, plastic STH-1a-125, corner design, blow-out angle 240° |
| 990 326 254 | 705 512 592 | 705 512 596 |



| Extract valve filter – 10 pieces | Ø 100mm supply valve housing | Ø 125mm supply valve housing |
|--|------------------------------|--|
| For Ø 100mm valve For Ø 125mm valve | With 2 x Ø 75mm ports | With 2 x Ø 75mm ports With 3 x Ø 75mm ports |
| 990 320 031 990 320 032 | TPSV1002 | TPSV1252 TPSV1253 |



Air Distribution Cleaning Set
990 000 106



Follow us on Twitter 

Follow us for the latest news, regulations, technical tips and the #SMARTest range of low energy ventilation products in the UK.

Follow us @greenwoodairvac