


Zehnder ComfoPipe Plus Twin Duct

Low profile ducting system



Features and benefits












- Low profile design – only 20cm space required above the ComfoAir 180
- Excellent thermal insulation
- Employs a combination of axial and radial sealing to ensure a strong, airtight connection
- Converts easily to Flat 51 ducting for all of the supply and return duct runs
- Exhausts to a unique 2-in-1 external grille for additional space saving benefits

Dimensions

Height: 200mm

Width: 330mm

Length: 400mm

<p>Zehnder ComfoPipe Plus twin duct Length 400mm</p> <p>990 328 800</p> 	<p>Switching unit For vertical/horizontal direction changes</p> <p>990 328 803</p> <p><i>Includes 2 end caps</i></p> 	<p>Horizontal 90° connection unit</p> <p>Right-hand 990 328 801 Left-hand 990 328 802</p> 
<p>Vertical connection unit</p> <p>990 328 805</p> 	<p>Joining set Connects twin duct to Ø 125mm pipe</p> <p>990 328 807</p> 	<p>Length compensation element Ensures spaces between ducting elements are filled</p> <p>990 328 808</p> 
<p>Fixing bracket Wide Narrow</p> <p>990 328 814 990 328 815</p> 	<p>Spacing rail For vertical installation above a unit</p> <p>990 328 816</p> 	<p>Short attenuator Length 568mm</p> <p>990 328 818</p> 
<p>Long attenuator Left, length 712mm Right, length 712mm</p> <p>990 328 819 990 328 820</p> 	<p>Combined external wall grille Right, Ø 125 to 200 m³/h Left, Ø 125 to 200 m³/h</p> <p>990 430 591 990 430 592</p> 	<p>Square extract valve Ø 90, plastic, white, fits to long attenuator</p> <p>990 326 253</p> 