


# Steel Ducting

*Spiral wound galvanised steel system*



## Features and benefits

- Available with a range of diameters from 100–200mm
- Wide selection of components for whole house ducting networks
- Designed to simply connect together on-site
- Robust ducting solution ideal for whole house continuous systems


## Size options

- Ø 100mm
- Ø 125mm
- Ø 150mm
- Ø 200mm


## Installation

- 1 Cut components to length as required
- 2 Join together with appropriate gasket connector
- 3 Support with perforated steel banding at 1 metre intervals
- 4 Gasket seals remove the need for adhesive tapes or sealants

Spiral duct – 3m length		90° bend – gasket seal		45° bend – gasket seal	
Ø 100mm	ST100	Ø 100mm	B90100G	Ø 100mm	B45100G
Ø 125mm	ST125	Ø 125mm	B90125G	Ø 125mm	B45125G
Ø 150mm	ST150	Ø 150mm	B90150G	Ø 150mm	B45150G
Ø 200mm	ST200	Ø 200mm	B90200G	Ø 200mm	B45200G



Male duct connector – gasket seal		Female bend connector		90° T-piece – gasket seal	
Ø 100mm	MC100G	Ø 100mm	FC100	Ø 100mm	PT100100G
Ø 125mm	MC125G	Ø 125mm	FC125	Ø 125mm	PT125125G
Ø 150mm	MC150G	Ø 150mm	FC150	Ø 150mm	PT150150G
Ø 200mm	MC200G	Ø 200mm	FC200		



Supply valve		Extract valve		Fire rated extract valve	
Ø 100mm	KE100	Ø 100mm	KSO100	Ø 100mm	KSOP100
Ø 125mm	KE125	Ø 125mm	KSO125	Ø 125mm	KSOP125
Ø 150mm	KE150	Ø 150mm	KSO150	Ø 150mm	KSOP150



Male to male reducer – gasket seal		Duct mounted attenuator	
Ø 100mm to Ø 80mm	CR10080G	Ø 100mm, L 600mm	CA100600
Ø 125mm to Ø 100mm	CR125100G	Ø 125mm, L 600mm	CA125600
Ø 125mm to Ø 80mm	CR12580G	Ø 150mm, L 600mm	CA150600
Ø 150mm to Ø 100mm	CR150100G	Ø 160mm, L 600mm	CA160600
Ø 150mm to Ø 125mm	CR150125G	Ø 200mm, L 600mm	CA200600
Ø 200mm to Ø 180mm	CR200180G	Ø 160mm, L 900mm	CA160900

