

# PIV Ducting

Modular PVC ducting system

## Features and benefits

- Non-corrosive light, rigid PVC for simple quick installation
- Versatile range of components for use with PIV PP2FLAT units
- Easy to install

## Physical specification

Rectangular system 121mm x 60mm

Material: White PVC



## Installation

- 1 Cut components to length as required
- 2 Slide together and pin through mounting straps to ceiling slab
- 3 Use non-hardening sealant to join components
- 4 Fits with PP2FLAT, PP2FLATHR, PP2FLATHL



| Rectangular duct |            | Connector | Mounting clip |           |
|------------------|------------|-----------|---------------|-----------|
| Length 1m        | PP2-4010WH |           | PP2-420WH     | PP2-422WH |
| Length 1.5m      | PP2-4015WH |           |               |           |




| 90° horizontal bend | 90° vertical bend | Rectangular to round 90° bend |                              |
|---------------------|-------------------|-------------------------------|------------------------------|
| PP2-450WH           |                   | PP2-460WH                     | Fits to Ø 100mm<br>PP2-430WH |



| Rectangular to round adaptor        | Rectangular flexible duct | Flexible duct connector |                        |
|-------------------------------------|---------------------------|-------------------------|------------------------|
| Fits to Ø 100mm<br>Fits to OD 100mm | Length 3m                 | PP2-471WH<br>PP2-470WH  | PP2-433WH<br>PP2-481WH |



| Low resistance fixed louvre | Mounting kit                                                                      | Two position switch |           |
|-----------------------------|-----------------------------------------------------------------------------------|---------------------|-----------|
| Fits to Ø 100mm             | For joint installation of all PP1 units, (supplied as standard with heater model) | PP1AVMOUNT          | PP1SWITCH |



**For internal use**  
Louvres point upwards

**For external use**  
Louvres point downwards

Provides high speed functionality for occupants, use with PP1 and PP2 units